

# Product specification

<b>Product</b>	<b>24AWG CAT5E UTP STRANDED 4P</b>	<b>NO.</b>		<b>Page</b>	<b>1/1</b>
<b>Edition</b>	<b>3</b>	<b>Established Date</b>	<b>2006-10-24</b>	<b>Revised Date</b>	<b>2006-10-25</b>
<b>Approval</b>		<b>Checked</b>		<b>Finish</b>	<b>Morganmiu</b>

## Configuration & Physical Characters:

<b>1.</b>	<b>Conductor</b>	<b>Material</b>	<b>Bare Copper</b>			
		<b>Construction</b>	<b>7/0.20 ± 0.025mm</b>			
<b>2.</b>	<b>Insulation</b>	<b>Material</b>	<b>HD-PE</b>			
		<b>Thickness</b>	<b>MIN at any point: 0.15mm MAX AVG:0.20 mm</b>			
		<b>Diameter</b>	<b>0.95 ± 0.03</b>			
		<b>Colors</b>	<b>Blue-White/Blue</b>			
			<b>Orange-White/Orange</b>			
			<b>Green-White/Green</b>			
<b>Brown-White/Brown</b>						
		_____				
		_____				
<b>3.</b>	<b>Jacket</b>	<b>Material</b>	<b>PVC</b>			
		<b>Thickness</b>	<b>MIN at any point: 0.40mm MAX AVG: 0.53mm</b>			
		<b>Diameter</b>	<b>5.3 ± 0.3</b>			
		<b>Colors</b>	<b>Assorted upon request</b>			
				_____		
				_____		
		<b>Marking</b>	<b>According to production specification</b>			

section chart:

bare copper

insulation

jacket