

Basic PDU

PE0112 Series

- The PE0112 series Basic PDU contains 12 AC outlets and is available in IEC or NEMA socket configurations. The PE0112 series Basic PDU features a space-saving 1U design that allows it to be mounted vertically on the outside of a rack, resulting in a more efficient use of space in the server room, while providing 12 AC outlets.


PE0112A Front View



PE0112G Front View



Diagram



Features

Basic PDU

- Space saving — 1U rack mount design
- EC or NEMA outlet models
- Overcurrent Protection
- Aluminum material

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Specifications

Function	PE0112A	PE0112G
Electrical		
Nominal Input Voltage	100-120 VAC	100-240 VAC
Maximum Input Current	15A Max, (UL derating 12A Max)	10A Max
Input Frequency	50-60 Hz	50-60 Hz
Input Connection	IEC-320 C14	IEC-320 C14
Input Power	IEC-320 C13 / NEMA 5-15P	IEC-320 C13 / IEC-320 C14
Outlet Type	(12) NEMA 5-15R	(12) IEC 320 C13
Maximum Output Current (Outlet)	15A Max (UL derating 12A Max)	10A max
Maximum Output Current (Bank)	15A Max (UL derating 12A Max)	10A max
Maximum Output Current (Total)	15A Max, (UL derating 12A Max)	10A max
OPD (Overcurrent Protection Device)	Yes	Yes
Physical Properties		
Dimensions (L x W x H)	48.80 x 4.40 x 4.50 cm	48.80 x 4.40 x 4.50 cm
Weight	0.62kg	0.62kg
Power Cord Length	10ft (14#)	10ft (3x1.0mm ²)
Environmental		
Temperature (Operating / Storage)	0 – 40°C / -20 – 60°C	0 – 40°C / -20 – 60°C
Elevation	3000m	3000m
Compliance		
EMC Verification	FCC Class A	CE Class A
Safety Verification		CE,LVD

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 10/2018 V1.0



© Copyright 2018 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.